

SR-1009 Series RF receiver

SR-1009FA-4x5A
SR-1009FA3-4x350mA
SR-1009FA7-4x700mA

SR-1009FAWi-4x5A
SR-1009FA3Wi-4x350mA
SR-1009FA7Wi-4x700mA

SR-1009CS-1x8A
SR-1009CS3-1x350mA
SR-1009CS7-1x700mA

SR-1009EA-4x8A

SR-1009FA(WP)-4x5A
SR-1009FA3(WP)-4x350mA
SR-1009FA7(WP)-4x700mA

SR-1009FAWi(WP)-4x5A
SR-1009FA3Wi(WP)-4x350mA
SR-1009FA7Wi(WP)-4x700mA

SRP-1009-CC

SRP-1009-12-50W CV
SRP-1009-24-50W CV
SRP-1009-36-50W CV

SR-1009AC-2x1.2A

SR-1009PD-4x5A
SR-1009PD3-4x350mA
SR-1009PD7-4x700mA

SR-1009P-4x5A
SR-1009P3-4x350mA
SR-1009P7-4x700mA

SR-1009SAC

SR-2818WiN
WiFi to RF Transmitter

SR-2818WiTR
WiFi to RF Transmitter

RF Control Application Diagram



SR-1009 Series RF sender

SR-2818

SR-2819T

SR-2819T8

SR-2819

SR-2839WK

SR-2858Z4-5C

SR-2858Z4

SR-2833K4

SR-2833K5

SR-2833N-Z5

SR-2819DIM

SR-2833TS

SR-2833S

SR-2819CCT

SR-2833TS-CCT

SR-2820B
(Size:EU/IT/US)

SR-2830C
(Size:EU/IT/US)

SR-2834-5C
(Size:EU/US)

SR-2830RGB
(Size:EU/IT/US)

SR-2831

SR-2831S

SR-2836RGB
(Size:EU/IT/US)

SR-2836DRGB

SR-2833RGB

SR-2835ST

SR-2836CCT
(Size:EU/IT/US)

SR-2834CCT
(Size:EU/US)

SR-2830B
(Size:EU/IT/US)

SR-2836DCCT

SR-2833K1

SR-2833K2

SR-2834RGBW
(Size:EU/US)

SR-2836R
(Size:EU/IT/US)

SR-2853-K2

SR-2853-K4

SR-2833T1
(Size:EU/IT/US)

SR-2833T2
(Size:EU/IT/US)

SR-2830A
(Size:EU/IT/US)

SR-2836D

SR-2833P

RF&Wifi Receiver



- 868MHz/433MHz/915MHz
- 4 channels output
- RF receiver
- Constant voltage/constant current

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS (mm)
SR-1009FA	12-36VDC	4CH,5A/CH	240-720W	Constant Voltage	46x178x18
SR-1009FA3	12-36VDC	4CH,0.35A/CH	16.8-50.4W	Constant Current	46x178x18
SR-1009FA7	12-36VDC	4CH,0.7A/CH	33.6-100.8W	Constant Current	46x178x18



- 868MHz/433MHz/915MHz
- 4 channels output
- RF receiver
- Constant voltage

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS (mm)
SR-1009EA	12-36VDC	4CH,8A/CH	384-1152W	Constant Voltage	58x168x28



- 868MHz/433MHz/915MHz
- 4 channels output
- RF/WiFi receiver
- Constant voltage/constant current

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS (mm)
SR-1009FAWi	12-36VDC	4CH,5A/CH	240-720W	Constant Voltage	57x178x21
SR-1009FA3Wi	12-36VDC	4CH,0.35A/CH	16.8-50.4W	Constant Current	57x178x21
SR-1009FA7Wi	12-36VDC	4CH,0.7A/CH	33.6-100.8W	Constant Current	57x178x21



- 868MHz/433MHz/915MHz
- 1 channel output
- Push switch
- RF receiver
- Constant voltage/constant current

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS (mm)
SR-1009CS	12-36VDC	1CH,8A/CH	96-288W	Constant Voltage	37x95x20
SR-1009CS3	12-36VDC	1CH,0.35A/CH	4.2-12.6W	Constant Current	37x95x20
SR-1009CS7	12-36VDC	1CH,0.7A/CH	8.4-25.2W	Constant Current	37x95x20



- 868MHz/433MHz/915MHz
- 4 channels output
- Guide rail installation
- RF receiver
- Constant voltage

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS (mm)
SR-1009Din	12-36VDC	4CH,5A/CH	240-720W	Constant Voltage	53x110x65

RF&Wifi Receiver



- 868MHz/433MHz/915MHz
- 4 channels output
- Waterproof (IP67)
- RF receiver
- Constant voltage/constant current

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS (mm)
SR-1009FA(WP)	12-36VDC	4CH,5A/CH	240-720W	Constant Voltage	73.6x180.5x38
SR-1009FA3(WP)	12-36VDC	4CH,0.35A/CH	16.8-50.4W	Constant Current	73.6x180.5x38
SR-1009FA7(WP)	12-36VDC	4CH,0.7A/CH	33.6-100.8W	Constant Current	73.6x180.5x38



- 868MHz/433MHz/915MHz
- 4 channels output
- Waterproof (IP67)
- RF/WiFi receiver
- Constant voltage/constant current

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS (mm)
SR-1009FAWi(WP)	12-36VDC	4CH,5A/CH	240-720W	Constant Voltage	73.6x180.5x38
SR-1009FA3Wi(WP)	12-36VDC	4CH,0.35A/CH	16.8-50.4W	Constant Current	73.6x180.5x38
SR-1009FA7Wi(WP)	12-36VDC	4CH,0.7A/CH	33.6-100.8W	Constant Current	73.6x180.5x38



- DC input
- 4 channels output
- RF receiver,868MHz/433MHz/915MHz
- Constant voltage/constant current

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS (mm)
SR-1009P	12-36VDC	4CH,5A/CH	240-720W	Constant Voltage	53.4x166x23
SR-1009P3	12-36VDC	4CH,0.35A/CH	16.8-50.4W	Constant Current	53.4x166x23
SR-1009P7	12-36VDC	4CH,0.7A/CH	33.6-100.8W	Constant Current	53.4x166x23



- DC input
- 4 channels output
- Repeater signal
- RF receiver,868MHz/433MHz/915MHz
- Constant voltage/constant current

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS (mm)
SR-1009PD	12-36VDC	4CH,5A/CH	240-720W	Constant Voltage	53.4x166x23
SR-1009PD3	12-36VDC	4CH,0.35A/CH	16.8-50.4W	Constant Current	53.4x166x23
SR-1009PD7	12-36VDC	4CH,0.7A/CH	33.6-100.8W	Constant Current	53.4x166x23



- 868MHz/433MHz/915MHz
- 5 channels output
- RF receiver
- Constant voltage

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS (mm)
SR-1009EA-5C	12-36VDC	5CH,8A/CH	480-1440W	Constant Voltage	58x168x28

RF Controller

RF & Wifi Single Color Controller



1 zone RF RGBW Controller

- 256 levels of Grey Scale per RGB, smooth for full-color changes without any flash.
- 10 changing modes. Enable to stay at any color under situation of color changing modes
- R-G-B-W changing colors can be achieved smoothly by buttons
- To adjust brightness of each color independently that can achieve millions of changing colors.
- To work with power repeater to expand output unlimitedly.

Part No.	Operation Voltage	Operation Frequency	Dimension (mm)
SR-2853K8-RGBW	3VDC	434MHz/868MHz/915MHz	55.5x55.5x13



RF&Wifi CCT Controller

- Ideal for white/ warm white to achieve precise adjustment of the color temperature and brightness
- Each white can achieve 256 levels brightness adjustment
- Remote control with 20 meters control distance
- Memory function, remember the last Kelvin after turn off/ or cut off
- To work with power repeater to expand output unlimitedly
- Enable be dimmed, switch ON/OFF and adjust color temperature by push button


Part No.	Operation Voltage	Operation Frequency	Dimension (mm)
SR-2853K4-CCT	3VDC	434MHz/868MHz/915MHz	55.5x55.5x13



RF&Wifi RGB+CCT Controller

- 5 channels RGB+CCT remote controller
- 256 levels of Grey Scale per RGB / CCT, smooth for full-color changes without any flash.
- 10 changing modes. Enable to stay at any color under situation of color changing modes
- R-G-B changing colors can be achieved smoothly by buttons
- To adjust brightness of each color independently that can achieve millions of changing colors.
- To work with power repeater to expand output unlimitedly.

Part No.	Operation Voltage	Operation Frequency	Dimension (mm)
SR-2853K8-5C	3VDC	434MHz/868MHz/915MHz	55.5x55.5x13



Remote

Part No.	Operation Voltage	Operation Frequency	DIMENSIONS (mm)	REMARKS
SR-2819DIM	4.5VDC	434MHz/868MHz/915MHz	48x140x17	6 zones single color remote

Receiver

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS (mm)
SR-1009FA	12-36VDC	4CH,5A/CH	240-720W	Constant Voltage	46x178x18
SR-1009FA3	12-36VDC	4CH,0.35A/CH	16.8-50.4W	Constant Current	46x178x18
SR-1009FA7	12-36VDC	4CH,0.7A/CH	33.6-100.8W	Constant Current	46x178x18
SR-1009EA	12-36VDC	4CH,8A/CH	384-1152W	Constant Voltage	58x168x28

- High sensitive & high stable touch color wheel ,fast &precise color control
- Touch the color wheel to choose the brightness you like
- Control 6 different zones separately or synchronously
- Can save 6 different scenes you like for each zone
- Control range max 20m.
- Each white can achieve 256 levels brightness adjustment, so there are millions of color temperature optional
- Dim brightness with 0.1% to 100%
- Memory function, remember the last Kelvin after turn off/ or cut off
- To work with power repeater to expand output unlimitedly
- Each receiver maximally be controlled by 8 different remote controllers
- Receivers can work with WiFi-RF converter after installing software on IOS and Android system.

RF&Wifi RGBW Wall Mounted Controller



Remote

Part No.	Operation Voltage	Operation Frequency	DIMENSIONS (mm)	REMARKS
SR-2820	12-24VDC/ 100-230VAC	434MHz/868MHz/915MHz	86x86x29.1	4 zones RGBW remote
SR-2820(IT)	12-24VDC/ 100-230VAC	434MHz/868MHz/915MHz	120x80x29.2	4 zones RGBW remote
SR-2820(US3)	12-24VDC/ 100-230VAC	434MHz/868MHz/915MHz	75x120x29.5	3 zones RGBW remote

Receiver

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS (mm)
SR-1009FA	12-36VDC	4CH,5A/CH	240-720W	Constant Voltage	46x178x18
SR-1009FA3	12-36VDC	4CH,0.35A/CH	16.8-50.4W	Constant Current	46x178x18
SR-1009FA7	12-36VDC	4CH,0.7A/CH	33.6-100.8W	Constant Current	46x178x18
SR-1009EA	12-36VDC	4CH,8A/CH	384-1152W	Constant Voltage	58x168x28

- User-friendly interface, easy and simple operation.
- Control 4 zones, each receiver maximally be controlled by 8 different remotes.
- Preset 10 changing modes, with pause function.
- Synchronization function of pattern changes ensure consistent change forever.
- Receivers can work with WIFI-RF converter after installing software on IOS and Android system.
- Enable to dim brightness of each R, G, B, W channel, in order to mix millions colors.
- Italian/ Australian, US , Europe size wall mounted size available as well.

RF&Wifi RGBW Wall Mounted Controller



Remote


Part No.	Operation Voltage	Operation Frequency	DIMENSIONS (mm)	REMARKS
SR-2820B	12-24VDC/ 100-230VAC	434MHz/868MHz/915MHz	86x86x29.1	1 zone RGBW touch remote
SR-2820B(IT)	12-24VDC/ 100-230VAC	434MHz/868MHz/915MHz	120x80x29.2	1 zone RGBW touch remote
SR-2820(US)	12-24VDC/ 100-230VAC	434MHz/868MHz/915MHz	75x120x29.5	1 zone RGBW touch remote

Receiver

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS (mm)
SR-1009FA	12-36VDC	4CH,5A/CH	240-720W	Constant Voltage	46x178x18
SR-1009FA3	12-36VDC	4CH,0.35A/CH	16.8-50.4W	Constant Current	46x178x18
SR-1009FA7	12-36VDC	4CH,0.7A/CH	33.6-100.8W	Constant Current	46x178x18
SR-1009EA	12-36VDC	4CH,8A/CH	384-1152W	Constant Voltage	58x168x28

- User-friendly interface, easy and simple operation.
- Operation return function.
- Control 1 zone, each receiver maximally be controlled by 8 different remotes.
- Preset 10 changing modes, with pause function.
- Synchronization function of pattern changes ensure consistent change forever.
- Receivers can work with WIFI-RF converter after installing software on IOS and Android system.
- Enable to dim brightness of each R, G, B, W channel, in order to mix millions colors.
- Italian/ Australian, US , Europe size wall mounted size available as well.

RF&Wifi RGB Controller



Remote

Part No.	Operation Voltage	Operation Frequency	DIMENSIONS (mm)	REMARKS
SR-2830RGB	12-24VDC/ 100-230VAC	434MHz/868MHz/915MHz	86x86x29.1	4 zones RGB remote
SR-2830RGB(IT)	12-24VDC/ 100-230VAC	434MHz/868MHz/915MHz	120x80x29.2	4 zones RGB remote
SR-2830RGB(US)	12-24VDC/ 100-230VAC	434MHz/868MHz/915MHz	75x120x29.5	4 zones RGB remote

Receiver

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS (mm)
SR-1009FA	12-36VDC	4CH,5A/CH	240-720W	Constant Voltage	46x178x18
SR-1009FA3	12-36VDC	4CH,0.35A/CH	16.8-50.4W	Constant Current	46x178x18
SR-1009FA7	12-36VDC	4CH,0.7A/CH	33.6-100.8W	Constant Current	46x178x18
SR-1009EA	12-36VDC	4CH,8A/CH	384-1152W	Constant Voltage	58x168x28

- Humanization design - with backlight indicating
- High sensitive & high stable Glass touch color line ,fast &precise color control
- Touch the color line to choose the color you like
- Control 4 zones separately or synchronously
- Save 1 color/scene you like for each zone
- Memory function, remember the last brightness after turn off/ or cut off
- Each white can achieve 256 levels brightness adjustment
- Control range max 20m.
- To work with power repeater to expand output unlimitedly
- Each receiver maximally be controlled by 8 different remote controllers
- Italian/Australia, American , Europe size size optional
- Receivers can work with WiFi-RF converter after installing software on IOS and Android system.

RF&Wifi RGB &Dual Color Controller



Remote

Part No.	Operation Voltage	Operation Frequency	DIMENSIONS (mm)	REMARKS
SR-2830C	12-24VDC/ 100-230VAC	434MHz/868MHz/915MHz	86x86x29.1	4 zones RGB+CCT remote
SR-2830C(IT)	12-24VDC/ 100-230VAC	434MHz/868MHz/915MHz	86x86x29.2	4 zones RGB+CCT remote
SR-2830C(US)	12-24VDC/ 100-230VAC	434MHz/868MHz/915MHz	86x86x29.5	4 zones RGB+CCT remote

Receiver

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS (mm)
SR-1009FA	12-36VDC	4CH,5A/CH	240-720W	Constant Voltage	46x178x18
SR-1009FA3	12-36VDC	4CH,0.35A/CH	16.8-50.4W	Constant Current	46x178x18
SR-1009FA7	12-36VDC	4CH,0.7A/CH	33.6-100.8W	Constant Current	46x178x18
SR-1009EA	12-36VDC	4CH,8A/CH	384-1152W	Constant Voltage	58x168x28

- Humanization design - with backlight indicating
- High sensitive & high stable Glass touch color line ,fast &precise color control
- Touch the color line to choose the color/color temperature
- Control 4 zones separately or synchronously
- Save 1 color/scene you like for each zone
- Memory function, remember the last brightness after turn off/ or cut off
- Each white can achieve 256 levels brightness adjustment
- Control range max 20m.
- To work with power repeater to expand output unlimitedly
- Each receiver maximally be controlled by 8 different remote controllers
- Italian/Australia, American , Europe size optional
- Receivers can work with WiFi-RF converter after installing software on IOS and Android system.

RF&Wifi RGB&Single Color Controller



Remote

Part No.	Operation Voltage	Operation Frequency	DIMENSIONS (mm)	REMARKS
SR-2830C1	12-24VDC/100-230VAC	434MHz/868MHz/915MHz	86x86x29.1	4 zones RGB+single color
SR-2830C1(IT)	12-24VDC/100-230VAC	434MHz/868MHz/915MHz	120x80x29.2	4 zones RGB+single color
SR-2830C1(US)	12-24VDC/100-230VAC	434MHz/868MHz/915MHz	75x120x29.5	4 zones RGB+single color

Receiver

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS (mm)
SR-1009FA	12-36VDC	4CH,5A/CH	240-720W	Constant Voltage	46x178x18
SR-1009FA3	12-36VDC	4CH,0.35A/CH	16.8-50.4W	Constant Current	46x178x18
SR-1009FA7	12-36VDC	4CH,0.7A/CH	33.6-100.8W	Constant Current	46x178x18
SR-1009EA	12-36VDC	4CH,8A/CH	384-1152W	Constant Voltage	58x168x28

- Humanization design - with backlight indicating
- High sensitive & high stable Glass touch color line ,fast &precise color control
- Touch the color line to choose the color you like
- Control 4 zones separately or synchronously
- Save 1 color/scene you like for each zone
- Memory function, remember the last brightness after turn off/ or cut off
- Each white can achieve 256 levels brightness adjustment
- Control range max 20m.
- To work with power repeater to expand output unlimitedly
- Each receiver maximally be controlled by 8 different remote controllers
- Italian/Australia, American , Europe size optional
- Receivers can work with WiFi-RF converter after installing software on IOS and Android system.

RF&Wifi RGBW Controller



Remote


Part No.	Operation Voltage	Operation Frequency	DIMENSIONS (mm)	REMARKS
SR-2831	12-24VDC/100-230VAC	434MHz/868MHz/915MHz	86x86x29.1	4 zones RGBW remote
SR-2831S	12-24VDC/100-230VAC	434MHz/868MHz/915MHz	86x86x29.1	1 zone RGBW remote

Receiver

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS o/h (mm)
SR-1009FA	12-36VDC	4CH,5A/CH	240-720W	Constant Voltage	46x178x18
SR-1009FA3	12-36VDC	4CH,0.35A/CH	16.8-50.4W	Constant Current	46x178x18
SR-1009FA7	12-36VDC	4CH,0.7A/CH	33.6-100.8W	Constant Current	46x178x18
SR-1009EA	12-36VDC	4CH,8A/CH	384-1152W	Constant Voltage	58x168x28

- Humanization design - with backlight indicating
- High sensitive & high stable Glass touch color panel ,fast &precise color control
- Touch the color panel to choose the color you like
- Control 4 zones separately or synchronously
- Save 1 color/scene you like
- Memory function, remember the last brightness after turn off/ or cut off
- Each white can achieve 256 levels brightness adjustment
- Control range max 20m.
- To work with power repeater to expand output unlimitedly
- Each receiver maximally be controlled by 8 different remote controllers
- Receivers can work with WiFi-RF converter after installing software on IOS and Android system.

RF&Wifi RGB+dual Color Controller



Remote


Part No.	Operation Voltage	Operation Frequency	DIMENSIONS (mm)	REMARKS
SR-2834-5C	12-24VDC/ 100-230VAC	434MHz/868MHz/915MHz	86x86x29.1	1 zone RGB+dual color
SR-2834-5C(US)	12-24VDC/ 100-230VAC	434MHz/868MHz/915MHz	75x120x29.5	1 zone RGB+dual color

Receiver

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS (mm)
SR-1009EA-5C	12-36VDC	5CH,8A/CH	480-1440W	Constant Voltage	59x170x29

- 5 channels: RGB+ dual color RF remote
- Humanization design - with backlight indicating
- High sensitive & high stable Glass touch color line ,fast &precise color control
- Touch the color line to choose the color you like
- Control 1 zone
- Memory function, remember the last brightness after turn off/ or cut off
- Control range max 20m.
- To work with power repeater to expand output unlimitedly
- Receivers can work with WiFi-RF converter after installing software on IOS and Android system.

RF&Wifi RGBW Controller



Remote

Part No.	Operation Voltage	Operation Frequency	DIMENSIONS (mm)	REMARKS
SR-2834RGBW	12-24VDC/ 100-230VAC	434MHz/868MHz/915MHz	86x86x29.1	1 zone RGBW touch remote
SR-2834RGBW(US)	12-24VDC/ 100-230VAC	434MHz/868MHz/915MHz	75x120x29.5	1 zone RGBW touch remote

Receiver

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS (mm)
SR-1009FA	12-36VDC	4CH,5A/CH	240-720W	Constant Voltage	46x178x18
SR-1009FA3	12-36VDC	4CH,0.35A/CH	16.8-50.4W	Constant Current	46x178x18
SR-1009FA7	12-36VDC	4CH,0.7A/CH	33.6-100.8W	Constant Current	46x178x18
SR-1009EA	12-36VDC	4CH,8A/CH	384-1152W	Constant Voltage	58x168x28

- Humanization design - with backlight indicating
- High sensitive & high stable Glass touch color line ,fast &precise color control
- Touch the color line to choose the color you like
- Control 1 zone
- Memory function, remember the last brightness after turn off/ or cut off
- Control range max 20m.
- To work with power repeater to expand output unlimitedly
- Receivers can work with WiFi-RF converter after installing software on IOS and Android system.

RF&Wifi Dual Color Controller



Remote

Part No.	Operation Voltage	Operation Frequency	DIMENSIONS (mm)	REMARKS
SR-2834CCT	12-24VDC/ 100-230VAC	434MHz/868MHz/915MHz	86x86x29.1	1 zone dual color remote
SR-2834CCT(US)	12-24VDC/ 100-230VAC	434MHz/868MHz/915MHz	75x120x29.5	1 zone dual color remote

Receiver

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS (mm)
SR-1009FA	12-36VDC	4CH,5A/CH	240-720W	Constant Voltage	46x178x18
SR-1009FA3	12-36VDC	4CH,0.35A/CH	16.8-50.4W	Constant Current	46x178x18
SR-1009FA7	12-36VDC	4CH,0.7A/CH	33.6-100.8W	Constant Current	46x178x18
SR-1009EA	12-36VDC	4CH,8A/CH	384-1152W	Constant Voltage	58x168x28

- Humanization design - with backlight indicating
- High sensitive & high stable Glass touch color line ,fast &precise color control
- Touch the color line to choose the color you like
- Control 1 zone
- Memory function, remember the last brightness after turn off/ or cut off
- Control range max 20m.
- To work with power repeater to expand output unlimitedly
- Receivers can work with WiFi-RF converter after installing software on IOS and Android system.

RF&Wifi RGB Controller



Remote

Part No.	Operation Voltage	Operation Frequency	DIMENSIONS (mm)	REMARKS
SR-2836RGB	3VDC	434MHz/868MHz/915MHz	86x86x29.1	1 zone RGB remote
SR-2836DRGB	3VDC	434MHz/868MHz/915MHz	65x96x80	1 zone RGB remote
SR-2836RGB(IT)	3VDC	434MHz/868MHz/915MHz	120x80x29.2	1 zone RGB remote
SR-2836RGB(US)	3VDC	434MHz/868MHz/915MHz	75x120x29.5	1 zone RGB remote

Receiver

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS o/h (mm)
SR-1009FA	12-36VDC	4CH,5A/CH	240-720W	Constant Voltage	46x178x18
SR-1009FA3	12-36VDC	4CH,0.35A/CH	16.8-50.4W	Constant Current	46x178x18
SR-1009FA7	12-36VDC	4CH,0.7A/CH	33.6-100.8W	Constant Current	46x178x18
SR-1009EA	12-36VDC	4CH,8A/CH	384-1152W	Constant Voltage	58x168x28

- Reliable & stable switch and dimming control function, control range max 20m.
- Battery in the remote is with long life span. It normally can use for 2 years.
- Switch on/off of lightings slowly, without any flash, meet the comfort of human eyes.
- Dimming range 0.1-100%.
- Enable to switch from color dimming to adjust RGB colors.
- Use with power repeater to expand the output power unlimitedly.
- Rotary adjustment, wall mounted panel/ table laying panel
- Italian/ Australian, US ,Europe size available for wall mounted
- Receivers can work with WiFi-RF converter after installing software on IOS and Android system.

Single Zone RF RGB Controller




Remote

Part No.	Operation Voltage	Operation Frequency	DIMENSIONS (mm)	REMARKS
SR-2833RGB	3VDC CR2430 battery	434MHz/868MHz/915MHz	86x86x10.1	1 zone RGB remote

Receiver

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS (mm)
SR-1009FA	12-36VDC	4CH,5A/CH	240-720W	Constant Voltage	46x178x18
SR-1009FA3	12-36VDC	4CH,0.35A/CH	16.8-50.4W	Constant Current	46x178x18
SR-1009FA7	12-36VDC	4CH,0.7A/CH	33.6-100.8W	Constant Current	46x178x18
SR-1009EA	12-36VDC	4CH,8A/CH	384-1152W	Constant Voltage	58x168x28

This is a RF Wireless Push Remote, can be wall mounted, or sticked on wall easily by 3M glue.



RF&Wifi Single Color & Dual Color & RGB Controller



Remote

Part No.	Operation Voltage	Operation Frequency	DIMENSIONS (mm)	REMARKS
SR-2835DIM	3VDC	434MHz/868MHz/915MHz	86x86x26.9	1 zone rotary single color
SR-2835CDW	3VDC	434MHz/868MHz/915MHz	86x86x26.9	1 zone rotary dual color
SR-2835RGB	3VDC	434MHz/868MHz/915MHz	86x86x26.9	1 zone rotary RGB color

Receiver

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS (mm)
SR-1009FA	12-36VDC	4CH,5A/CH	240-720W	Constant Voltage	46x178x18
SR-1009FA3	12-36VDC	4CH,0.35A/CH	16.8-50.4W	Constant Current	46x178x18
SR-1009FA7	12-36VDC	4CH,0.7A/CH	33.6-100.8W	Constant Current	46x178x18
SR-1009EA	12-36VDC	4CH,8A/CH	384-1152W	Constant Voltage	58x168x28

- Special rotary design easy operation
- Ideal for single color, dual color and RGB LED lighting
- Turn left/right to adjust brightness, color temperature and RGB color tone.
- Enable to connect with single color, dual color and RGB LED lighting to achieve precise adjustment of brightness, color temperature and RGB color tone.
- Independent brightness adjustment of each color
- Control range max 20m.
- Memory function, remember the last Kelvin after turn off/ or cut off
- To work with power repeater to expand output unlimitedly
- Each receiver maximally be controlled by 8 different remote controllers
- Italian/Australia, American size optional
- With free stickers on the back easy to be installed and uninstalled
- Receivers can work with WIFI-RF converter after installing software on IOS and Android system.

Single Zone RF RGB/CCT/Single color Controller



SR-2836N

SR-2836N-RGB

SR-2835N-CCT

Remote

Part No.	Operation Voltage	Operation Frequency	DIMENSIONS (mm)	REMARKS
SR-2836N	12-24VDC/100-230VAC	434MHz/868MHz/915MHz	80x80x53	1 zone rotary single color
SR-2836N-RGB	12-24VDC/100-230VAC	434MHz/868MHz/915MHz	80x80x53	1 zone rotary RGB color
SR-2835N-CCT	12-24VDC/100-230VAC	434MHz/868MHz/915MHz	80x80x53	1 zone rotary dual color

Receiver

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS (mm)
SR-1009FA	12-36VDC	4CH,5A/CH	240-720W	Constant Voltage	46x178x18
SR-1009FA3	12-36VDC	4CH,0.35A/CH	16.8-50.4W	Constant Current	46x178x18
SR-1009FA7	12-36VDC	4CH,0.7A/CH	33.6-100.8W	Constant Current	46x178x18
SR-1009EA	12-36VDC	4CH,8A/CH	384-1152W	Constant Voltage	58x168x28

- Special rotary design easy operation
- Single color, dual color and RGB color version for choose
- Turn left/right to adjust brightness, color temperature and RGB color tone.
- Independent brightness adjustment of each color
- Control range max 20m.
- Memory function, remember the last color after turn off/ or cut off
- To work with power repeater to expand output unlimitedly
- Each receiver maximally be controlled by 8 different remote controllers

RF Single Color & Dual Color & RGB Controller



Remote

Part No.	Operation Voltage	Operation Frequency	DIMENSIONS (mm)	REMARKS
SR-2835N	3VDC	434MHz/868MHz/915MHz	81x81x30	1 zone rotary single color
SR-2835N-CCT	3VDC	434MHz/868MHz/915MHz	81x81x30	1 zone rotary dual color
SR-2835N-RGB	3VDC	434MHz/868MHz/915MHz	81x81x30	1 zone rotary RGB color

Receiver

Part No.	Input Voltage	Output current	Output Power	Output Type	DIMENSIONS (mm)
SR-1009FA	12-36VDC	4CH,5A/CH	240-720W	Constant Voltage	46x178x18
SR-1009FA3	12-36VDC	4CH,0.35A/CH	16.8-50.4W	Constant Current	46x178x18
SR-1009FA7	12-36VDC	4CH,0.7A/CH	33.6-100.8W	Constant Current	46x178x18
SR-1009EA	12-36VDC	4CH,8A/CH	384-1152W	Constant Voltage	58x168x28

- Special rotary design easy operation
- Ideal for single color, dual color and RGB LED lighting
- Turn left/right to adjust brightness, color temperature and RGB color tone.
- Independent brightness adjustment of each color
- Control range max 20m.
- Memory function, remember the last color after turn off/ or cut off
- To work with power repeater to expand output unlimitedly
- Each receiver maximally be controlled by 8 different remote controllers
- With free stickers on the back easy to be installed and uninstalled
- Receivers can work with WIFI-RF converter after installing software on IOS and Android system.